

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
15 March 2001 (15.03.2001)

PCT

(10) International Publication Number
WO 01/17692 A1

- (51) International Patent Classification⁷: **B05C 11/00**, H05H 1/10 (72) Inventor: **RAAIJMAKERS, Ivo**; Jan van Eycklaan 10, NL-3723 BC Bilthoven (NL).
- (21) International Application Number: **PCT/US00/24586** (74) Agents: **DOUGHTY, Susan, K. et al.**; Greenlee, Winner and Sullivan, P.C., Suite 201, 5370 Manhattan Circle, Boulder, CO 80303 (US).
- (22) International Filing Date:
8 September 2000 (08.09.2000) (81) Designated States (*national*): JP, KR.
- (25) Filing Language: English (84) Designated States (*regional*): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).
- (26) Publication Language: English
- (30) Priority Data:
09/392,371 8 September 1999 (08.09.1999) US **Published:**
— *With international search report.*
- (71) Applicant: **ASM AMERICA, INC.** [US/US]; 3440 East University Drive, Phoenix, AZ 85034-7200 (US). *For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*



WO 01/17692 A1

(54) Title: **IMPROVED APPARATUS AND METHOD FOR GROWTH OF A THIN FILM**

(57) Abstract: An improved apparatus and method for substrate layer deposition in which substrate layers are grown by carrier gas (C, D) delivery of sequential pulses of reactants (A, B) to the substrate surfaces. (5) At least one of the reactants (A, B) comprises excited species, e.g., radicals. In a specific embodiment, the apparatus of this invention provides sequential repeated pulses of reactants in a flow of carrier gas (4, 13) for reaction at a substrate surfaces. The reactant pulses are delivered with sufficient intervening delay times to minimize undesirable reaction between reactants (A, B) in adjacent pulses in the gas phase or undesired uncontrolled reactions on the substrate surface (5).

IMPROVED APPARATUS AND METHOD FOR GROWTH OF A THIN FILM

BACKGROUND OF THE INVENTION

This invention relates generally to improved apparatus and methods for deposition processes in the manufacture of semiconductor materials.

Chemical vapor deposition (CVD) processes have long been used to form thin layers on substrates (and wafers) by sequential layer deposition by thermal reaction or decomposition of gaseous material (reactants) at the substrate surface. In a specific type of deposition process, atomic layer epitaxy (ALE), sequential monolayers are deposited on a substrate surface by alternate exposure to chemical reactants. Repeated exposure cycles of the substrate to reactant gases builds the desired layer structure. ALE techniques are described for example in M. Ritala et al. (1998) J. ElectroChemical Society **145**: 2914; H. Shriniki et al. (1998) J. ElectroChemical Society **145**:3247 and J.L. Vossen et al. "Thin Film Deposition Processes II" (Academic Press, CA 1991). The terms ALE and "atomic layer chemical vapor deposition," ALCVD are considered equivalent in this disclosure.

A variety of apparatus have been employed for layer deposition processes. A basic system includes a reactant chamber, a substrate holder with a heater, a gas flow system including gas inlets for providing reactants to the substrate surface and an exhaust system for removing used gases.

Deposition apparatus are configured for batch processing of multiple substrates or single-substrate processing. Single-substrate processing is presently more preferred for larger substrates to improve uniformity of deposition. Horizontal gas flow reactors, such as described in Ozias U.S. patents 4,846,102; 5,096,534; and 5,244,694 which concentrate reactant gas flow at the substrate surface and particularly those equipped with gas manifolds that create uniform reactant gas velocity profiles (Hawkins et al. U.S. patent 5,221,556) provide efficient uniform processing of large single substrates.

ALCVD deposition processes, particularly as practiced in horizontal flow reactors for single wafer processing, are performed in a step-wise manner, in which a first reactant is introduced into the reaction chamber through a gas inlet or manifold to form a deposited layer on the substrate. Excess reactant gas is then evacuated from the reaction chamber in a pump-down step (see for example, Sherman, U.S. Patent No. 5,916,365). Optionally, an inert purge gas is flowed through the gas inlet to remove residual reactant. After the pump down, a second reactant is introduced into the chamber to react with the deposited reactant to form the desired substrate layer. Excess reactant is then removed in another pump-down step. Layers are added to the substrate surface by sequential additions of various reactant gases with intervening chamber pump-down. Step-wise processing with chamber evacuation is employed to separate reactant gases and minimize reaction of these gases in the gas phase or in parts of the reaction chamber other than on the substrate to avoid formation of particles that are detrimental to substrate processing and to avoid depletion of reactants. Intervening chamber evacuation steps represent a significant portion of the time required for processing a substrate, in most cases exceeding 50%. A significant decrease in process time leading to a significant decrease in manufacturing cost could be achieved by eliminating the chamber evacuation steps.

Suntola et al. U.S. patent 4,389,973 and U.S. patent 5,711,811 describe apparatus for ALE of a substrate in which sequentially applied reactant gases are separated by inert gas phase diffusion barriers. For example, timed pulses of reactant gases are transported into a reaction chamber to interact with the substrate in a continuous flow of carrier gas passing through the chamber. Reactant gases are thus applied separately to the substrate in a continuous gas flow without need of intervening chamber evacuations. U.S. patents 4,747,367 and 4,761,269 (Crystal Specialties) describe chemical vapor deposition methods in which a constant flow and pressure of gas is maintained on sequentially pulsing of reactant gases into a neutral carrier gas stream. When a reactant gas is switched into or out of the carrier gas flow, the carrier gas flow is decreased or increased, respectively, to maintain constant flow and pressure in the reaction chamber. It is important to note that

these techniques work only at sufficiently high pressures (>10 torr), where diffusion in the gas phase is sufficiently low.

It is known in substrate deposition processes to employ excited species, particularly radicals, to react with and/ or decompose chemical species at the substrate surface to form the deposited layer. In processes using activated species, the apparatus is provided with a device for excitation. Radicals can, for example, be generated (along with ions) by application of RF or microwave energy to form a plasma. A number of alternative methods for formation of radicals are known in the art, including, for example, thermal decomposition and photolysis.

Reactive species, including radicals, can be generated *in situ* in the reactant chamber at or near the substrate surface or generated remotely and subsequently carried, e.g., by gas flow, to the reaction chamber. See, U.S. patents 4,664,937, 4,615,905 and 4,517,223 for *in situ* radical generation and U.S. 5,489,362 for remote radical generation. Remote radical generation allows exclusion of potentially undesirable reactive species (e.g., ions) that may be detrimental to substrate processing. However, remote radical generation techniques should provide sufficient radical densities at the substrate surface, notwithstanding the significant losses that can occur on transport of the radical to the reaction chamber. Radical losses are generally severe at higher pressure (> 10 Torr), thus precluding the use of higher pressure to separate the reactants in an ALE process.

20

SUMMARY OF THE INVENTION

25

The present invention provides an improved apparatus and method for substrate layer deposition in which substrate layers are grown by carrier gas delivery of sequential pulses of reactants to the substrate surface. At least one of the reactants comprises excited species, e.g., radicals. In a specific embodiment, the apparatus of this invention provides sequential repeated pulses of reactants in a flow of carrier gas for reaction at a substrate surface. The reactant pulses are delivered with sufficient intervening delay times to minimize undesirable reaction between reactants in adjacent pulses in the gas phase or undesired uncontrolled

reactions on the substrate surface. We have found that depending on reactor design, there is a pressure range where sufficient excited species, including radicals, survive and where an inert gas phase diffusion barrier can be used.

In a more specific embodiment, the present invention provides an improved apparatus and method for substrate layer deposition that combines a horizontal flow reactor chamber having uniform gas flow parallel to and concentrated at the substrate surface with continuous flow carrier gas delivery of sequential concentration pulses of reactants to the substrate surface.

The use of reactant pulses separated in time and space in a carrier gas flow significantly increases the speed of processing because intervening chamber pump down steps are not required. Use of the methods and apparatus of this invention results in high layer growth rates typically greater than about 1 -10 nm/min.

In general the method of this invention can be employed in any reaction chamber designed for thin film growth, including among others horizontal flow reactors, vertical furnaces, and stagnant flow reactors, as long as recirculation of reactant gases is minimized.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a schematic illustration of a reaction chamber of this invention provided with a microwave plasma generator remote from the chamber.

Figures 2A and B are a schematic illustration of alternate reaction chambers of this invention. Figure 2A is a reaction chamber with an R excited species generator in the reaction chamber. Figure 2B is a reaction chamber with an excited species generator in the gas inlet line.

Figures 3A-C are graphs of reactant concentration as a function of distance x along a flow path through the reaction chamber schematically illustrating the progress of sequential pulses of reactants A and B* (containing radicals) in the same

carrier gas flow through an apparatus of this invention. Fig. 3A illustrates the reactant pulses at time t_0 just as a peak of B^* enters the reaction chamber at $x = 0$, where x is the distance along the reaction chamber. The graph illustrates that the concentration pulse travels in the positive x direction due to convection, and broadens with time and distance due to diffusion. Fig. 3B illustrates the A and B^* reactant concentration pulses of Fig. 3A at a time $t = t_0 + 1/2(L_R/v)$ where L_R is the length of the reaction chamber and v is the gas velocity. Fig. 3B illustrates a more preferred embodiment of this invention wherein the pulses of reactants A and B^* are sufficiently separated in time and space that there is no overlap of the reactant pulses in the carrier gas flow. No gas phase or uncontrolled reaction should occur in this case. Fig. 3C illustrates a different timing sequence of reactant pulses for the method of this invention indicating a maximum reactant pulse overlap that is typically sufficiently low to avoid undesired reactions.

DETAILED DESCRIPTION OF THE SPECIFIC EMBODIMENTS

The invention is further described by reference to the figures in which the same numbers indicate like features.

Figure 1 illustrates a deposition apparatus of this invention adapted for delivery of sequential pulses of two different reactants A and B^* , one of which B^* contains excited species, to a substrate. The apparatus has a reaction chamber 10 with substrate 5 positioned on holder 15 which is optionally heated. The substrate holder can be heated resistively, inductively or by use of infrared lamps, as is known in the art. Gases flow into the reactor through one or more gas inlets 4 at the injector flange 6. Residual gases, after passage over the substrate are removed through an exhaust conduit 12 provided with a throttle valve 14 and a pressure measurement and control 14A. The reactor chamber illustrated is a radiantly heated, horizontal flow cold wall reactor, typically made of quartz, and having a divider plate 16 substantially aligned with the top surface of the substrate holder and separating the reaction chamber into upper and lower portions. The divider plate provides a substantially constant cross-section in the reaction area, thus, preventing

recirculation cells. In order to prevent reactants from reaching the bottom of the reaction chamber, a bottom purge 17 is provided.

A generator of excited species 20 is provided remotely and upstream from the reaction area, and preferably upstream from the chamber 10. Most generally this generator couples an energy source into a flow of a precursor molecule (or mixture to molecules) to generate excited species. In the illustrated embodiment, the generator 20 couples microwave energy from a magnetron to a gas line 8, so that the gas in inlet 7 contains excited species. Alternative generators suitable for use in this apparatus couple thermal energy or visible UV or IR radiation into a precursor. An exemplary microwave radical generator suitable for use in this invention is Rapid Reactive Radicals Technology, R³T, Munich, Germany, model number TWR850. Precursors B are introduced into the excited species generator, illustrated as a microwave plasma generator, through gas line 8. A source of second reactant (A) is provided in gas line 9. A source of carrier gas (C), a gas inert to the reactants and inert to the substrate, is provided in gas line 11. Each gas line is provided with separate mass flow controls (MFC) (21a, b and c) to allow selection of relative amounts of carrier, reactant and excited species B* introduced into the reaction chamber. Shut off valves (22a, b, c) to completely stop the flow of gas are provided in lines 11, 9 and 8. In Fig. 1, C is a carrier gas (e.g., typically N₂ or Ar), B is the precursor to the excited species (e.g., N₂, H₂, NH₃, O₂) and A is a second reactant gas. Reactant A line 9 is provided with a dump circuit 30a which is in selective communication with line 9 via two-way valve 27a. Precursor B line 8 is optionally provided with a similar dump circuit 30b, two-way valve 27b and inert carrier gas circuit D (22d, 21d), analogous to the circuit for C. In a preferred embodiment, no valves are provided in conduit 7 extending from the generator of excited species to the reaction chamber to minimize decay of excited species during transport to the reaction area. Moreover, in a preferred embodiment, the tube 7 is wide and short (approximately 2 cm in diameter x 15 cm long) to minimize wall losses of radicals. In another embodiment, excited species can be introduced in the main carrier gas stream 4, just before it enters in the reactor.

In operation to deposit sequential atomic layers formed by deposition of A followed by reaction of deposited A with excited species derived from B the following preferred procedure is used.

An unprocessed wafer is positioned on the holder in the reaction chamber, as is well known in the art. A main carrier gas C flow (13) is established into the reaction chamber (10) through MFC 21c, valve 22c and the injector flange (6) on the inlet side of the reaction chamber. Typically, in a 200-mm reactor with a cross-section of 50 cm², a flow of about 50 slm is used. The preferred gas flow is dependent on the design of the chamber and can be optimized without due experimentation. The pressure in the reaction chamber is preferably set at 0.5 to 100 Torr, and preferably 1-20 Torr, and more preferably 2-10 Torr, with conventional techniques using, for example, throttle valves (e.g., 14) and dry pumps (as known in the art, but not shown in Fig. 1). The temperature of the holder (susceptor) and substrate is controlled at a desired value by heating and thermocouple control, as is well known in the art. The optimum temperature is highly dependent on the reactants used. For the exemplary reactions discussed below, the temperature is typically in the range of about 200°C-500°C.

A flow of reactant A is established at a desired flow rate (typically, < 1slm, dependent upon the exact process chemistry) set by MFC 21a through valve 27a which is initially set to flow into dump circuit 30a. A flow of precursor gas B is established at a desired flow rate (typically a few slm, also dependent upon the exact process chemistry) set by MFC 21b through radical generator 20 via valve 22B. Flow through the generator of excited species may be a mixture of a precursor B in a carrier gas established by components D, 27d, 21d. Alternatively, precursor gas B can be a mixture of a carrier gas and a precursor gas. Initially the radical generator is not switched on, so only non-excited precursor gas is flowing through conduit 7 into the reaction chamber into the flow of carrier gas C. In one embodiment, where excited nitrogen species are employed, both carrier gas C and precursor gas B are nitrogen. In that case, the dump circuit 30b, and carrier gas supply D are not needed.

To begin a cycle of layer deposition, valve 27a is switched from the dump circuit to the reactor inlet for a predetermined time (t_A , typically ranging from a fraction of a second to several seconds) and then switched back to the dump circuit providing a concentration pulse of reactant A into the flow of carrier gas C. After a predetermined delay time (t_s^1), the radical generator is turned on to provide excited species B*, e.g. radicals, into the reaction chamber. The radical generator is kept on for a predetermined time (t_B , typically ranging from a fraction of a second to several seconds) and switched off to provide a pulse of excited species B*. After a predetermined delay time (t_s^2), the cycle of A and B* pulses is repeated, until a desired layer thickness is achieved. Note that t_s^2 can be different from t_s^1 . The microwave power used is generally on the order of 100W - 5kw, and more preferably, is in the range of 500W - 2kw. Note that in this preferred embodiment, the gas flow is almost constant, as B and C are flowing continuously and $A < C$, and $B^* < B$. After a wafer is processed, the chamber conditions (pressure, gas flow, and temperature) are adjusted, as is known in the art, to exchange the processed wafer for an unprocessed wafer and the processing cycle is repeated on the unprocessed wafer.

The delay times (e.g., t_s^1 and t_s^2) are adjusted to avoid undesirable levels of gas phase reaction and undesirable levels of uncontrolled reaction on the substrate surface. Undesirable levels of gas phase and uncontrolled surface reactions are those levels of reaction that result in unacceptable defects in the layers formed on the substrate. Such defects can render the processed substrate or wafer unuseable. Time scheduling of pulses of reactants can readily be determined for a given reaction system and reactants by routine experimentation, as will be understood in view of the present disclosure, and is further discussed below with reference to Figs. 3A-C. The delay times between pulses of reactants may be different and may change during processing if desired.

The apparatus of this invention can be provided with microprocessor and/or computer control for the automation of valves and for switching the generator of

excited species on and off to provide desired timed pulses of reactants. Such controls are known in the art and can be readily provided for a given apparatus.

The apparatus of this invention has a gas inlet system having one or more gas inlets into the reaction chamber which allow establishment of carrier gas flow into the reaction chamber and into contact with a substrate surface in the chamber.

5 The gas inlet system also allows introduction of one or more reactants including at least one reactant comprising excited species into the carrier gas flow which carries the reactants into contact with the substrate surface. Carrier gas flow is exhausted from the reaction chamber through a vacuum pump exhaust. The gas inlet system can have valves for generating concentration pulses of reactants. Preferably,
10 excited species can be generated remotely from the reaction chamber. Excited species can also be generated *in situ* in the reaction chamber, as is known in the art. In the preferred case, the gas inlet system provides a separate conduit for introducing excited species into the carrier gas flow. The excited species can also be introduced into the carrier gas flow just before it enters the chamber. In this
15 case, more losses of radicals are possible, but still enough radicals can be present to complete the reaction.

Although the invention is illustrated with a horizontal flow, cold wall reactor having a constant cross-section reaction area, other horizontal designs, such as hot wall reactors, can also be employed in the methods of this invention. Similarly, the
20 invention can be readily adapted for use with vertical batch reaction chambers and furnaces, such as those described in U.S. patents 5,294,572, 5,336,325 and 5,662,470. The invention can also be readily adapted for use in reaction chambers in which gas flow is delivered perpendicular (rather than parallel) to the substrate surface, for example through an inlet positioned above the substrate surface, such
25 as a shower head design. In each case, care is taken in reaction chamber design to avoid recirculation of reactants. Recirculation greatly enhances the residence time of reactive species which can lead to undesired gas phase reactions. Undesired gas phase reactions can lead to particle formation in the reaction chamber decreasing the quality of the layers formed on the substrate. Recirculation can be

especially harmful when it occurs upstream from the wafer as then it affects the deposition process. Care must also be taken to operate the excited species as close as practically possible to the chamber to assure sufficient survival of radicals.

Figure 2A illustrates an alternate reaction chamber 10 of this invention in which excited species are formed in the reaction chamber. In this case a showerhead inlet 40 is provided through which carrier flow and reactant gas pulses are established. A plasma can be generated by application of RF power electrically connected to the showerhead using an RF generator 42 coupled to an RF matching network, as is well-known in the art. Gas line 41 directs gases from gas manifolds into the showerhead inlet. A source of carrier gas C with valves and mass flow controller, as in the apparatus of Fig. 1, provides carrier gas flow into the chamber passing in contact with a substrate or wafer (5) on optionally heated holder 15 to exit through exhaust lines 12. A source of reactant A with valves, mass flow controller and dump circuit 30A, as in Fig. 1, provides concentration pulses of A into carrier gas C by timed operation of valve 27a. Pulses of A are alternated with pulses of RF power to generate alternate pulses of A and excited C* species. In this case, layers are formed by reaction of excited C* species with deposited A reactant. The pulses of A and C* are separated in time and space, as discussed above and in Figs. 3A - 3C below, to avoid an undesired level of gas phase or uncontrolled surface reactions. C can, for example, be nitrogen carrier gas and C* can be excited nitrogen species.

Plasmas may also be generated in the reaction chamber using RF coils as is known in the art. RF power can be modulated as is well-known in the art to provide concentration pulse of excited species. An alternate means for generating a plasma employing a showerhead -type inlet is disclosed in U.S. patent 5,134,965, which is incorporated by reference herein.

Figure 2B illustrates an alternative reactor design with remote plasma generation of excited species employing a showerhead inlet 40. An RF cavity or coil 47 is provided in the inlet line 41. RF power is applied from RF generator 42

through RF matching network 45 to generate a plasma in the inlet line 41. Excited species are formed in the inlet by pulsing the RF power on and off. Concentration pulses of excited species are carried into the reaction chamber in the carrier gas flow. The operation of RF generators and RF matching circuits are well-known in the art.

Figures 3A and 3B schematically illustrate, in one dimension (x), progress of gas pulses traversing the reaction chamber in graphs of reactant concentration as a function of flow distance through the reaction chamber. Fig. 3A is at time t_0 , just as a pulse of reactant B^* enters the reaction chamber (by, e.g., switching on the radical generator). At this time, an earlier pulse of A has traversed a distance equal to L_s (the distance traversed in delay time t_s between pulses of different reactant). In the drawing it is assumed that the time each of the gases is on is negligible compared to the delay time between gas pulses. L_D is the characteristic diffusion length, a measure of the broadening of the reactant pulse as a function of time due to gas diffusion where $L_D = 2\sqrt{Dt}$, where D is the diffusion coefficient of the reactant gas in the carrier and t is the residence time, where $t = L_R/D$. Fig. 3B illustrates the B^* pulse and A pulse at time $t_0 + 1/2(L_R/v)$. As indicated in these figures, pulses broaden due to diffusion of reactants when the pulses traverse the reaction chamber. Pulses illustrated in Fig. 3B are sufficiently separated in distance, despite pulse broadening, to avoid interaction and reaction of reactants in different pulses. L_R is the length of the reaction chamber and v is the flow velocity of the gas ($v=Q/pA$, where Q is the mass flow rate, p is the pressure in the reaction chamber and A is the cross-sectional area of the reactor). The delay t_s between pulses is preferably sufficiently long to minimize overlap of reactant gas pulses in the reactor chamber and minimize gas phase or uncontrolled surface reactions. Significant gas phase reactions or uncontrolled reactions on the surface are avoided when $L_D < L_s$, e.g., preferably where L_s is at least about 5 - 10 times L_D . It should be noted that short cycles are desirable to maximize the throughput of the reactor. The desire to minimize pulse overlap is a trade-off with increased throughput.

Table 1 presents the results of a calculation of L_s and t_s over the pressure range 0.2 - 20 Torr and N_2 gas flow rate (Q) range 1 - 50 slm, assuming $L_s = 10 L_D$. In most cases, the delay time (t_s) between pulses (e.g., the time between shutting of one reactant and admitting another reactant) is small, i.e., less than one second. The delay time exceeds one second only at the lowest flow and highest pressure. Thus, even when L_s is constrained to be $10 L_D$, reactant pulse sequences can follow each other in quite rapid succession, typically one every second, enabling a high layer growth rate. It should be noted that conditions do exist where $L_s \gg L_R$. Essentially this implies that one reactant is fully purged from the reactor before the other reactant is introduced.

Fig. 3B illustrates a pulse time scheme in which the time between pulses is sufficiently long that adjacent pulses of reactants do not overlap as they broaden and traverse the reaction chamber. In this case, the leading edge (LE_B) of one pulse does not overlap the trailing edge (TE_A) of the preceding pulse. Significant gas phase reactions are avoided when L_D is smaller (preferably 5-10 times smaller) than the distance between the trailing and leading edges of the pulses. Fig. 3C illustrates an embodiment where some overlap of reactant pulses is allowed. The amount of overlap illustrated in the figure typically does not result in levels of gas phase reaction or uncontrolled surface reaction that are high enough to detrimentally affect the quality of the layers formed on the substrate or wafer. The use of shorter delay times between pulses, so long as the quality of the layers is not detrimentally affected, is preferred to speed up processing times and thereby improve wafer throughput. Reactant pulse overlap can be characterized in terms of the relative concentration of the reactants at a given point in time, space or both during flow through the reactor. A preferred maximum overlap is defined as follows.

At any point in time or space where the concentration of reactant A is at its maximum (M_A), the concentration of reactant B* at that same point is less than about 10% of the maximum concentration of B* (M_B) and at any point in time or space where the concentration of reactant B* is at its maximum (M_B), the concentration of reactant A at that same point is less than about 10% of the

maximum concentration of A (M_A). Delay times selected to meet this maximum overlap criterium typically provide sufficiently clean layer deposition and decreased process times. In certain cases where more reactive chemistries are employed for layer deposition, the maximum overlap should be decreased to avoid undesired reactions which can affect layer quality. In such cases, the maximum concentrations of reactants A and B* at the maximum concentrations of B* and A, respectively, is 1% or less.

Generally, it is preferred that the pulse reactant system is operated under conditions that minimize diffusion, i.e., at high flow velocity. Delay times t_s between pulse of gas are selected as described above to avoid or minimize undesired gas phase reaction between reactants and undesired uncontrolled surface reactions and to minimize processing time. The preferred carrier gas or gases used are non-reactive with any reactants that are to be used in a given process and also non-reactive with the substrate surface. Examples are N_2 , H_2 , noble gases and mixtures of these, the choice of which depends upon the process choice or precursors and exposed layers. Reactant gases include pure reactant gases, a mixture of reactants, excited species (e.g., radicals) or mixtures of excited neutrals and mixtures of excited neutrals with diluent or carrier gas. Reactants are typically introduced into the reaction chamber in a carrier gas. Reactants are in the vapor phase when introduced into the reaction chamber.

In a cycle, consisting of one pulse of each reactant with appropriate delay times between pulses, one monolayer or less is typically grown (on the order of about 0.03 - 0.3 nm/ layer). Practical films useful in semiconductor applications range in thickness from about 1 to about 50 nm. Processing times in a single wafer processing apparatus for practical films will require about 6-600 s for the illustrated reactor.

The process cycle of layer deposition has been exemplified with sequential pulses of two reactants, one of which contains excited species. The apparatus and method of this invention can be employed in formation of complex layers requiring

more than two reactants (including reactants containing excited or activated species or radicals). The schedule or order of multiple reactant pulses employed in this invention can be sequential or readily adapted to any order of reactant pulsing for a wide variety of deposition or layering processes. The method of this invention has been exemplified with sequential pulses of reactant separated by a selected delay time (t_s) and of selected pulse duration (t_A and t_B). The delay time between pulses of reactants can be varied over the course of multiple cycles, so long as the delay time used is sufficient to avoid an undesirable level of gas phase or uncontrolled surface reaction among reactants. The pulse duration of the different reactants may be the same or different and will preferably be selected to achieve a desired level of surface reaction. The pulse duration of the same reactants over the course of multiple cycles of layer deposition may be the same or different and will also preferably be selected to achieve a desired level of surface reaction.

The reactant pulse schemes of Figs. 3A-C, illustrate multiple pulses carried in a single flow of carrier gas, such as illustrated in the apparatus of Fig. 1 or Fig. 2. In alternative embodiments, sequential pulses of reactants can be delivered to a reaction area containing one or more substrates in separate carrier gas flows.

Radicals or excited species useful in processing of substrates include, among others, active nitrogen (N^* , N_2^* , N_2^+ or mixtures thereof) generated by microwave discharge of nitrogen, oxygen radicals generated by microwave discharge of oxygen, radicals or reactive species generated by photolysis or thermal decomposition. Plasmas for radical generation can be generated by microwave or RF energy, as is well-known in the art. Radicals or excited species tend to recombine or decay into the non-excited state during transport to the reaction area through gas phase reactions and on the walls of conduits. Therefore, it is beneficial to install the radical generator as close as practical to the reaction area on the wafer surface. Further, the pressures during transport of the excited species cannot be too high. Successful generation and transport of radicals has been demonstrated at pressures up to about 50 torr in N_2 . Preferably the pressure in the apparatus of this invention is kept at about 5-10 torr.

Excited neutrals can include radicals, and atoms and molecules in excited electronic states. Excited neutrals can be generated in plasmas sustained by RF or microwave energy. Alternatively, they can be generated by irradiation of precursor neutral species at selected wavelengths including ultra-violet (U.V.), visible and infra-red (IR) wavelengths to decompose neutrals forming radicals and or excited states. Excited neutrals, particularly radicals, can also be formed by thermal decomposition of precursors.

The apparatus of this invention is preferably implemented with a microwave radical, excited neutrals generator which may be remote from the reactor chamber or within the reaction chamber. For applications in the pulsed reactant system, pressures are selected to be sufficiently high to facilitate ignition of a plasma as well as to limit diffusion of reactant pulses into each other to avoid undesired reactions. Pressures are also selected to be sufficiently low to avoid substantial decay of excited species or recombination of radicals so that practical levels of excited species reach the reaction area. Reactor pressures ranging from about 0.5 up to 10-20 Torr are preferred. A preferred microwave plasma source which provides high efficiency at these relatively low reactant pressures is described in Steinhardt et al. U.S. patent 5,489,362, and is commercially available from R³T, as noted above.

In a specific embodiment, the apparatus of this invention can be used to produce silicon nitride layers on silicon wafers. In this application, reactant A is SiH₄ using nitrogen as the carrier gas and the substrate is heated to about 300- 550°C. B* is active nitrogen generated by passing nitrogen through a microwave radical generator. Repeated sequential pulses of SiH₄ and active nitrogen grows a SiN layer of desired thickness.

In other specific embodiments:

(1) Tantalum oxide layers can be deposited on appropriate substrates employing the apparatus of this invention. In this application, reactant A is

volatile source of Ta, preferably tantalum pentaethoxide, using nitrogen carrier gas C and the substrate is heated to about 200°C-400°C. B* are oxygen radicals generated by passing oxygen source gas B, preferably O₂, through a microwave radical generator;

5 (2) Tantalum nitride layers can be deposited on appropriate substrates employing the apparatus of this invention. In this application, reactant A can be a volatile source of Ta, preferably pentakis(dimethylamino)tantalum using nitrogen carrier gas and the substrate is heated to about 200°C-400°C. B* are nitrogen or ammonia radicals, which may be generated by passing nitrogen or ammonia through a microwave radical generator. Alternatively, a
10 mixture of N₂ and H₂ can be passed through the radical generator. Tantalum nitride layers can be used, for example as a diffusion barrier in copper metallization;

(3) Titanium nitride layers can be deposited on appropriate substrates employing the apparatus of this invention. In this application, reactant A can
15 be a volatile, non-oxygen containing Ti source, preferably pentakis(dimethylamino)titanium, using nitrogen carrier gas and the substrate is heated to about 200°C-400°C. B* are nitrogen or ammonia radicals, which may be generated by passing nitrogen or ammonia through a microwave radical generator. Alternatively, a mixture of N₂ and H₂ can be passed
20 through the radical generator. Titanium nitride layers can be used, for example, as a diffusion barrier in aluminum-based metallization;

(4) Metal layers, such as Ta or Ti, can be deposited on appropriate substrates employing the apparatus of this invention. In this application, reactant A can be TaCl₅ or TiCl₄, for example, using nitrogen carrier gas and the substrate is
25 heated to about 200°C-400°C. B* are hydrogen radicals, which may be generated by passing hydrogen through a microwave radical generator.

In yet another specific embodiment, the apparatus of this invention can be employed in the growth of layers by selective adsorption of a reactant. For example, under certain conditions metal organic precursors or SiH_4 can be made to preferentially adsorb onto Si and not onto SiO_2 or SiN_4 . Exposure of the selectively adsorbed species on Si to radicals effectively completes reaction only on Si. Thus, a layer is grown only on the area of Si. Similar adsorption selectivity of reactants and selective layer growth can be achieved on metal areas (e.g., Cu or Al) with respect to dielectrics.

As noted above, the pulsed gas flow apparatus of this invention is preferably implemented in a horizontal flow reactor in a reactor system as described, for example, in Crabb et al. U.S. patents 4,828,224, 5, 156,521, 5,092,728, and 5,435,682. A variety of substrates and wafers of different sizes, shapes and materials can be processed by the apparatus and method of this invention. Substrates are positioned in a substrate holder (a susceptor) that is typically heated. A variety of substrate holders are known in the art. Multiple substrates can be processed simultaneously, for example, by stacking the wafers in a boat, positioning wafers laterally apart on a single susceptor or by having multiple susceptors for holding one or more wafers in a reaction chamber.

Those of ordinary skill in the art will recognize that reactants, precursors of excited species, materials, procedures, conditions and structures other than those specifically described herein can be employed in the practice of this invention without expense of undue experimentation. All known functional equivalents of the reactants, precursors, materials, procedures, conditions and structures specifically disclosed herein are intended to be encompassed by this invention.

All references cited herein are incorporated by reference in their entirety herein to the extent that they are not inconsistent with the disclosure herein.

Table 1

Gas flow Q (slm)	Area A(cm ²)	Pressure p(Torr)	Pumping speed S(L/s)	Gas velocity v(m/s)	Diffusion coeff. D(m ² /s)	Reactor length L _R (cm)	Time to traverse reactor t _R (s)	Diffusion length L _D (cm)	Diffusion/ reactor length L _D /L _R	Pulse spacing* L _S (cm)	Pulse timing* t _S (s)
50	50	0.2	3166.667	633.3333	0.05	20	0.000316	0.794719	0.039736	7.947194	0.000125
50	50	2	316.6667	63.33333	0.005	20	0.003158	0.794719	0.039736	7.947194	0.001255
50	50	20	31.66667	6.333333	0.0005	20	0.031579	0.794719	0.039736	7.947194	0.012548
5	50	0.2	316.6667	63.33333	0.05	20	0.003158	2.513123	0.125656	25.13123	0.003968
5	50	2	31.66667	6.333333	0.005	20	0.031579	2.513123	0.125656	25.13123	0.039681
5	50	20	3.166667	0.633333	0.0005	20	0.315789	2.513123	0.125656	25.13123	0.396809
1	50	0.2	63.33333	12.66667	0.05	20	0.015789	5.619515	0.280976	56.19515	0.044365
1	50	2	6.333333	1.266667	0.005	20	0.157895	5.619515	0.280976	56.19515	0.443646
1	50	20	0.633333	0.126667	0.0005	20	1.578947	5.619515	0.280976	56.19515	4.436459

*Calculated assuming L_S = 10 L_D

I claim:

1. An apparatus for growing a thin film which comprises:

- (a) a reaction chamber;
- (b) a substrate mounted in the reaction chamber;
- (c) a gas inlet system for establishing a carrier gas flow into the reaction chamber and for introducing one or more reactants into the carrier gas flow wherein at least one of the reactants comprises excited species;
- (d) a gas outlet.

wherein during operation of the chamber time separated pulses of reactants are introduced into the carrier gas such that a desired film is deposited on the substrate.

- 2. The apparatus of claim 1 further comprising a vacuum exhaust system in communication with the gas outlet.
- 3. The apparatus of claim 1 further comprising a generator of excited species for introduction into the carrier gas.
- 4. The apparatus of claim 1 wherein the pulses of reactants are sufficiently separated to minimize undesired reaction of reactant in adjacent pulses in the reaction chamber.
- 5. The apparatus of claim 1 wherein the pulses of reactants are sufficiently separated in time such that the characteristic diffusion length of the reactants sequential in the carrier gas (L_D) is smaller than the distance between the trailing and leading edges of the sequential pulses.

6. The apparatus of claim 5 wherein the pulses of reactants are sufficiently separated in time such that the characteristic diffusion length of the reactants in the carrier gas (L_D) is 5 to 10 times smaller than the distance between the trailing and leading edges of the sequential pulses.
- 5 7. The apparatus of claim 3 wherein the generator of excited species is a microwave radical generator.
8. The apparatus of claim 7 wherein the microwave radical generator is remote from the reaction chamber.
9. The apparatus of claim 3 wherein excited species are produced in a plasma generated in the reaction chamber.
- 10 10. The apparatus of claim 1 wherein pulses of a reactant without excited species alternate with pulses of a reactant comprising excited species.
11. The apparatus of claim 3 wherein the gas inlet system comprises a first carrier gas inlet in communication with a reactant source, and a second gas inlet in communication with a generator of excited species.
- 15 12. The apparatus of claim 1 wherein the concentration of a reactant in a carrier gas flow at a point in space and time as it passes through the reaction chamber is no more than about 10% of its maximum value when at that point in space and time the concentration of a second reactant in a carrier gas flow is at its maximum value.
- 20 13. The apparatus of claim 1 wherein the concentration of a reactant in a carrier gas flow at a point in space and time as it passes through the reaction chamber is no more than about 1% of its maximum value when at that point in space and time the concentration of a second reactant in a carrier gas flow is at its maximum value.

14. The apparatus of claim 1 wherein alternating pulses of a reactant are carried in the same carrier gas flow.
15. The apparatus of claim 1 further comprising a control system to provide for the timing of pulses of reactants.
- 5 16. A method for depositing a layer on a substrate comprising the steps of:
- (a) providing a reaction chamber for receiving said substrate and for receiving a carrier gas;
 - (b) providing concentration pulses of reactants in the carrier gas, at least one of which contains excited species that are sufficiently separated in
10 time and space during transit through the reaction chamber to minimize undesired gas phase reactions or uncontrolled surface reactions;
 - (c) repeating the pulses of reactants until the desired layer thickness has been formed on the substrate surface.
- 15 17. The method of claim 16 where the layer thickness per cycle is less than about 1 nm.
18. The method of claim 16 wherein the concentration of any one reactant in a carrier flow at a point in space and time is no greater than 10% of its maximum value when at that same point in space, time, or both another
20 reactant is at its maximum concentration.
19. The method of claim 16 wherein the concentration of any one reactant in a carrier flow at a point in space and time is no greater than 1% of its maximum

value when at that same point in space and time another reactant is at its maximum concentration.

20. The method of claim 16 wherein the pulses of reactants are sufficiently separated in time such that the characteristic diffusion length of the reactants or excited species in the carrier gas (L_D) is smaller than the distance between the trailing and leading edges of the pulses.
21. The method of claim 16 wherein the pulses of reactants are sufficiently separated in time and space such that the characteristic diffusion length of the reactants or excited species in the carrier gas (L_D) is 5 to 10 times smaller than the distance between the trailing and leading edges of the pulses.
22. The method of claim 16 wherein the excited species are excited neutrals or radicals formed in a plasma.
23. The method of claim 16 wherein pulses of a reactant gas without excited species alternate with pulses of a reactant comprising excited species.
24. The method of claim 16 wherein the gas inlet system comprises a first gas inlet for introducing carrier gas flow into the reaction chamber and a second gas inlet for introducing reactants comprising excited species into said carrier gas flow.
25. The method of claim 16 wherein concentration pulses of the reactant containing excited species are generated by pulsing on an energy source coupled to a flow of precursor of the excited species.
26. The method of claim 24 where the energy source provides thermal energy.
27. The method of claim 24 wherein the energy source provides visible, UV or IR radiation.




FIG. 1





Fig. 2B

3 / 3




FIG. 3A




FIG. 3B




FIG. 3C

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US00/24586

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) : B05C 11/00, H05H 1/10

US CL : 118/696, 427/571

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 118/696, 427/571

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EAST

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 4,389,973 A (SUNTOLA et al) 28 June 1983, abstract, Figs. 1 and 2.	1-27
Y	US 4,761,269 A (CONGER et al) 02 August 1988, Fig. 1.	1-15
Y	US 5,166,092 A (MOCHIZUKI et al) 24 November 1992, Figs. 4-5 and 7-8; claims.	1-27
Y	US 5,270,247 A (SAKUMA et al) 14 December 1993, Fig. 9, col. 7 lines 15-50.	16-27
Y	US 5,693,139 A (NISHIZAWA et al) 02 December 1997, abstract, Fig. 9 and 11.	1-27



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be of particular relevance	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"E" earlier document published on or after the international filing date	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"&" document member of the same patent family
"O" document referring to an oral disclosure, use, exhibition or other means	
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

14 NOVEMBER 2000

Date of mailing of the international search report

27 DEC 2000

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

MATTHEW A. ANDERSON

Telephone No. (703) 308-0086

